

CERTIFICATE OF MAILING BY EXPRESS MAIL

"EXPRESS MAIL" Mailing Label No. EK 742 473 751 US
Date of Deposit: October 12, 2001
I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231

Type or Print Name: Annie N. Mathew

Signature *Annie N. Mathew*

A SYSTEM AND METHOD FOR REAL TIME RESERVOIR MANAGEMENT

The present application is a continuation-in-part of co-pending U.S. Patent Application Serial No. 09/816,044, filed March 23, 2001 which is a continuation of U.S. Patent No. 09/357426, filed July 20, 1999, both of which are hereby incorporated by reference in their entirety as if reproduced herein.

BACKGROUND

Historically, most oil and gas reservoirs have been developed and managed under timetables and scenarios as follows: a preliminary investigation of an area was conducted using broad geological methods for collection and analysis of data such as seismic, gravimetric, and magnetic data, to determine regional geology and subsurface reservoir structure. In some instances, more detailed seismic mapping of a specific structure was

conducted in an effort to reduce the high cost, and the high risk, of an exploration well. A test well was then drilled to penetrate the identified structure to confirm the presence of hydrocarbons, and to test productivity. In lower-cost onshore areas, development of a field would commence immediately by completing the test well as a production well. In higher cost or more hostile environments such as the North Sea, a period of appraisal would follow, leading to a decision as to whether or not to develop the project. In either case, based on inevitably sparse data, further development wells, both producers and injectors would be planned in accordance with a reservoir development plan. Once production and/or injection began, more dynamic data would become available, thus, allowing the engineers and geoscientists to better understand how the reservoir rock was distributed and how the fluids were flowing. As more data became available, an improved understanding of the reservoir was used to adjust the reservoir development plan resulting in the familiar pattern of recompletion, sidetracks, infill drilling, well abandonment, etc. Unfortunately, not until the time at which the field was abandoned, and when the information is the least useful, did reservoir understanding reach its maximum.

Limited and relatively poor quality of reservoir data throughout the life of the reservoir, coupled with the relatively high cost of most types of well intervention, implies that reservoir management is as much an art as a science. Engineers and geoscientists responsible for reservoir management discussed injection water, fingering, oil-water contacts rising, and fluids moving as if these were a precise process. The reality, however, is that water expected to take three years to break through to a producing well might arrive in six months in one reservoir but might never appear in another. Text book "piston like" displacement rarely happens, and one could only guess at flood patterns.

For some time, reservoir engineers and geoscientists have made assessments of reservoir characteristics and optimized production using down hole test data taken at selected intervals. Such data usually includes traditional pressure, temperature and flow data is well known in the art. Reservoir engineers have also had access to production data for the individual wells in a reservoir. Such data as oil, water and gas flow rates are generally obtained by selectively testing production from the selected well at selected intervals.

Recent improvements in the state of the art regarding data gathering, both down hole and at the surface, have dramatically

increased the quantity and quality of data gathered. Examples of such state of the art improvements in data acquisition technology include assemblies run in the casing string comprising a sensor probe with optional flow ports that allow fluid inflow from the formation into the casing while sensing wellbore and/or reservoir characteristics as described and disclosed in international PCT application WO 97/49894, assigned to Baker Hughes, the disclosure of which is incorporated herein by reference. The casing assembly may further include a microprocessor, a transmitting device, and a controlling device located in the casing string for processing and transmitting real time data. A memory device may also be provided for recording data relating to the monitored wellbore or reservoir characteristics. Examples of down hole characteristics which may be monitored with such equipment include: temperature, pressure, fluid flow rate and type, formation resistivity, cross-well and acoustic seismometry, perforation depth, fluid characteristics and logging data. Using a microprocessor, hydrocarbon production performance may be enhanced by activating local operations in additional downhole equipment. A similar type of casing assembly used for gathering data is described and illustrated in international PCT application WO 98/12417,

assigned to BP Exploration Operating Company Limited, the disclosure of which is incorporated by reference.

Recent technology improvements in downhole flow control devices are disclosed in UK Patent Application GB 2,320,731A which describes a number of downhole flow control devices which may be used to shut off particular zones by using downhole electronics and programing with decision making capacity, the disclosure of which is incorporated by reference.

Another important emerging technology that may have a substantial impact on managing reservoirs is time lapsed seismic, often referred to a 4-D seismic processing. In the past, seismic surveys were conducted only for exploration purposes. However, incremental differences in seismic data gathered over time are becoming useful as a reservoir management tool to potentially detect dynamic reservoir fluid movement. This is accomplished by removing the non-time varying geologic seismic elements to produce a direct image of the time-varying changes caused by fluid flow in the reservoir. By using 4-D seismic processing, reservoir engineers can locate bypassed oil to optimize infill drilling and flood pattern. Additionally, 4-D seismic processing can be used to enhance the reservoir model and history match flow simulations.

International PCT application WO 98/07049, assigned to Geo-Services, the disclosure of which is incorporated herein by reference, describes and discloses state of the art seismic technology applicable for gathering data relevant to a producing reservoir. The publication discloses a reservoir monitoring system comprising: a plurality of permanently coupled remote sensor nodes, wherein each node comprises a plurality of seismic sensors and a digitizer for analog signals; a concentrator of signals received from the plurality of permanently coupled remote sensor nodes; a plurality of remote transmission lines which independently connect each of the plurality of remote sensor nodes to the concentrator, a recorder of the concentrated signals from the concentrator, and a transmission line which connects the concentrator to the recorder. The system is used to transmit remote data signals independently from each node of the plurality of permanently coupled remote sensor nodes to a concentrator and then transmit the concentrated data signals to a recorder. Such advanced systems of gathering seismic data may be used in the reservoir management system of the present invention as disclosed hereinafter in the Detailed Description section of the application.

Historically, down hole data and surface production data has been analyzed by pressure transient and production analysis.

Presently, a number of commercially available computer programs such as Saphir and PTA are available to do such an analysis. The pressure transient analysis generates output data well known in the art, such as permeability-feet, skin, average reservoir pressure and the estimated reservoir boundaries. Such reservoir parameters may be used in the reservoir management system of the present invention.

In the past and present, geoscientists, geologists and geophysicists (sometimes in conjunction with reservoir engineers) analyzed well log data, core data and SDL data. The data was and may currently be processed in log processing/interpretation programs that are commercially available, such as Petroworks and DPP. Seismic data may be processed in programs such as Seisworks and then the log data and seismic data are processed together and geostatistics applied to create a geocellular model.

Presently, reservoir engineers may use reservoir simulators such as VIP or Eclipse to analyze the reservoir. Nodal analysis programs such as WEM, Prosper and Openflow have been used in conjunction with material balance programs and economic analysis programs such as Aries and ResEV to generate a desired field wide production forecast. Once the field wide production has been forecasted, selected wells may be produced at selected

rates to obtain the selected forecast rate. Likewise, such analysis is used to determine field wide injection rates for maintenance of reservoir pressure and for water flood pattern development. In a similar manner, target injection rates and zonal profiles are determined to obtain the field wide injection rates.

It is estimated that between fifty and seventy percent of a reservoir engineer's time is spent manipulating data for use by each of the computer programs in order for the data gathered and processed by the disparate programs (developed by different companies) to obtain a resultant output desired field wide production forecast. Due to the complexity and time required to perform these functions, frequently an abbreviated incomplete analysis is performed with the output used to adjust a surface choke or recomplete a well for better reservoir performance without knowledge of how such adjustment will affect reservoir management as a whole.

SUMMARY OF THE INVENTION

The present invention comprises a field wide management system for a petroleum reservoir on a real time basis. Such a field wide management system includes a suite of tools (computer programs) that seamlessly interface with each other to generate

a field wide production and injection forecast. The resultant output of such a system is the real time control of downhole production and injection control devices such as chokes, valves and other flow control devices and real time control of surface production and injection control devices. Such a system and method of real time field wide reservoir management provides for better reservoir management, thereby maximizing the value of the asset to its owner.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosed invention will be described with reference to the accompanying drawings, which show important sample embodiments of the invention and which are incorporated in the specification hereof by reference. A more complete understanding of the present invention may be had by reference to the following Detailed Description when taken in conjunction with the accompanying drawings, wherein:

FIGURE 1 is a block diagram of the method of field wide reservoir management of the present invention;

FIGURE 2 is a cross section view of a typical well completion system that may be used in the practice of the present invention;

FIGURE 3 is a cross section of a flat back cable that may be used to communicate data from sensors located in a wellbore to the data management and analysis functions of the present invention and communicate commands from the reservoir management system of the present invention to adjust downhole well control devices;

FIGURE 4 is a block diagram of the system of real time reservoir management of the present invention; FIGURE 4 is a generalized diagrammatic illustration of one exemplary embodiment of the system of FIGURE 4;

FIGURE 5 illustrates exemplary operations which can be performed by the controller of FIGURE 4A to implement the data management function of FIGURE 4;

FIGURE 6 illustrates exemplary operations which can be performed by the controller of FIGURE 4A to implement the nodal analysis function and the material balance function of FIGURE 4;

FIGURE 7 illustrates exemplary operations which can be performed by the controller of FIGURE 4A to implement the reservoir simulation function of FIGURE 4; and

FIGURE 8 illustrates exemplary operations which can be performed by the controller of FIGURE 4A to implement the risk economics function of FIGURE 4.

DETAILED DESCRIPTION

Reference is now made to the Drawings wherein like reference characters denote like or similar parts throughout the Figures.

Referring now to FIGURES 1 and 4, the present invention comprises a method and system of real time field wide reservoir management. Such a system includes a suite of tools (computer programs of the type listed in Table 1) that seamlessly interface with each other in accordance with the method to generate a field wide production and injection forecast. It will be understood by those skilled in the art that the practice of the present invention is not limited to the use of the programs disclosed in Table 1. Programs listed in Table 1 are merely some of the programs presently available for practice of the invention.

The resultant output of the system and method of field wide reservoir management is the real time control of downhole production and injection control devices such as chokes, valves, and other flow control devices (as illustrated in FIGURES 2 and 3 and otherwise known in the art) and real time control of surface production and injection control devices (as known in the art). The real time control described herein need not necessarily be instantaneous, but can be delayed depending on

how the control is communicated to the downhole production and injection control devices. Field wide reservoir management does not require that every well in a field be controlled.

Efficient and sophisticated "field wide reservoir data" is necessary for the method and system of real time reservoir management of the present invention. Referring now to blocks 1, 2, 3, 5 and 7 of FIGURE 1, these blocks represent some of the types of "field wide reservoir data" acquired generally through direct measurement methods and with devices as discussed in the background section, or by methods well known in the art, or as hereinafter set forth in the specification. It will be understood by those skilled in the art that it is not necessary for the practice of the subject invention to have all of the representative types of data, data collection devices and computer programs illustrated and described in this specification and the accompanying Figures, nor is the present invention limited to the types of data, data collection devices and computer programs illustrated herein. As discussed in the background section, substantial advancements have been made and are continuing to be made in the quality and quantity of data gathered.

In order to provide for more efficient usage of "field wide reservoir data", the data may be divided into two broad areas:

production and/or injection (hereinafter "production/injection") data and geologic data. Production/injection data includes accurate pressure, temperature, viscosity, flow rate and compositional profiles made available continuously on a real time basis or, alternatively, available as selected well test data or daily average data.

Referring to box 18, production/injection data may include downhole production data 1, seabed production data 2 and surface production data 3. It will be understood that the present invention may be used with land based petroleum reservoirs as well as subsea petroleum reservoirs. Production/injection data is pre-processed using pressure transient analysis in computer programs such as Saphir by Kappa Engineering or PTA by Geographix to output reservoir permeability, reservoir pressure, permeability-feet and the distance to the reservoir boundaries.

Referring to box 20, geologic data includes log data, core data and SDL data represented by block 5 and seismic data represented by block 7. Block 5 data is pre-processed as illustrated in block 6 using such computer programs such as Petroworks by Landmark Graphics, Prizm by Geographix and DPP by Halliburton to obtain water and oil saturations, porosity, and clay content. Block 5 data is also processed in stratigraphy programs as noted in block 6A by programs such as Stratworks by

Landmark Graphics and may be further pre-processed to map the reservoir as noted in block 6B using a Z-Map program by Landmark Graphics.

Geologic data also includes seismic data block 7 that may be conventional or real time 4D seismic data (as discussed in the background section). Seismic data may be collected conventionally by periodically placing an array of hydrophones and geophones at selected places in the reservoir or 4D seismic may be collected on a real time basis using geophones placed in wells. Block 7 seismic data is processed and interpreted as illustrated in block 8 by such programs as Seisworks and Earthcube by Landmark Graphics to obtain hydrocarbon indicators, stratigraphy and structure.

Output from blocks 6 and 8 is further pre-processed as illustrated in block 9 to obtain geostatistics using Sigmapview by Landmark Graphics. Output from blocks 8, 9 and 6B are input into the Geocellular (Earthmode) programs illustrated by block 10 and processed using the Stratamodel by Landmark Graphics. The resultant output of block 10 is then upscaled as noted in block 11 in Geolink by Landmark Graphics to obtain a reservoir simulation model.

Output from upscaling 11 is input into the data management function of block 12. Production/injection data represented by

downhole production 1, seabed production 2 and surface production 3 may be input directly into the data management function 12 (as illustrated by the dotted lines) or pre-processed using pressure transient analysis as illustrated in block 4 as previously discussed. Data management programs may include Openworks, Open/Explorer, TOW/cs and DSS32, all available from Landmark Graphics and Finder available from Geoquest.

Referring to box 19 of FIGURE 1, wherein there is disclosed iterative processing of data gathered by and stored in the data management program. Reservoir simulation may be accomplished by using data from the data management function 12 using VIP by Landmark Graphics or Eclipse by Geoquest. Material Balance calculations may be performed using data from the reservoir simulation 13 and data management function 12 to determine hydrocarbon volumes, reservoir drive mechanisms and production profiles, using MBAL program of Petroleum Experts.

Nodal Analysis 15 may be performed using the material balance data output of 14 and reservoir simulation data of 13 and other data such as wellbore configuration and surface facility configurations to determine rate versus pressure for various system configurations and constraints using such

programs as WEM by P.E. Moseley and Associates, Prosper by Petroleum Experts, and Openflow by Geographix.

Risked Economics 16 may be performed using Aries or ResEV by Landmark Graphics to determine an optimum field wide production/injection rate. Alternatively, the target field wide production/injection rate may be fixed at a predetermined rate by factors such as product (oil and gas) transportation logistics, governmental controls, gas oil or water processing facility limitations, etc. In either scenario, the target field wide production/injection rate may be allocated back to individual wells.

After production/injection for individual wells is calculated the reservoir management system of the present invention generates and transmits a real time signal used to adjust one or more interval control valves located in one or more wells or adjust one or more subsea control valves or one or more surface production control valves to obtain the desired flow or injection rate. As above, transmission of the real time signal is not necessarily instantaneous, and can be delayed depending on the communication method. For example, the reservoir management system may signal an operator to adjust a valve. The operator may then travel into the field to make the adjustment or may telephone another operator near the valve to

make the adjustment. Also, it will be understood by those skilled in the art that an inter-relationship exists between the interval control valves. When one is opened, another may be closed. The desired production rate for an individual well may be input directly back into the data management function 12 and actual production from a well is compared to the target rate on a real time basis. The system may include programming for a band width of acceptable variances from the target rate such that an adjustment is only performed when the rate is outside the set point.

Opening or closing a control valve 17 to the determined position may have an almost immediate effect on the production/injection data represented by blocks 1, 2, 3; however, on a long term basis the reservoir as a whole is impacted and geologic data represented by blocks 5 and 7 will be affected (See dotted lines from control valve 17). The present invention continually performs iterative calculations as illustrated in box 19 using reservoir simulation 13, material balance 14, nodal analysis 15 and risked economics 16 to continuously calculate a desired field wide production rate and provide real time control of production/injection control devices.

The method on field wide reservoir management incorporates the concept of "closing the loop" wherein actual production data from individual wells and on a field basis.

To obtain an improved level of reservoir performance, downhole controls are necessary to enable reservoir engineers to control the reservoir response much like a process engineer controls a process facility. State of the art sensor and control technology now make it realistic to consider systematic development of a reservoir much as one would develop and control a process plant. An example of state of the art computers and plant process control is described in PCT application WO 98/37465 assigned to Baker Hughes Incorporated.

In the system and method of real time reservoir management of the present invention, the reservoir may be broken into discreet reservoir management intervals - typically a group of sands that are expected to behave as one, possibly with shales above and below. Within the wellbore, zonal isolation packers may be used to separate the producing and/or injection zones into management intervals. An example reservoir management interval might be 30 to 100 feet. Between zonal isolation packers, variable chokes may be used to regulate the flow of fluids into or out of the reservoir management interval.

U.S. Patent No. 5,547,029 by Rubbo, the disclosure of which is incorporated by reference, discloses a controlled reservoir analysis and management system that illustrates equipment and systems that are known in the art and may be used in the practice of the present invention. Referring now to FIGURE 2, one embodiment of a production well having downhole sensors and downhole control that has been successfully used in the Norwegian sector of the North Sea, the Southern Adriatic Sea and the Gulf of Mexico is the "SCRAMSJ" concept. It will be understood by those skilled in the art that the SCRAMSJ concept is one embodiment of a production well with sensors and downhole controls that may be used in practicing the subject invention. However, practice of the subject invention is not limited to the SCRAMSJ concept.

SCRAMSJ is a completion system that includes an integrated data-acquisition and control network. The system uses permanent downhole sensors and pressure-control devices as well known in the art that are operated remotely through a control network from the surface without the need for traditional well-intervention techniques. As discussed in the background section, continuous monitoring of downhole pressure, temperatures, and other parameters has been available in the industry for several decades, the recent developments providing

for real-time subsurface production and injection control create a significant opportunity for cost reductions and improvements in ultimate hydrocarbon recovery. Improving well productivity, accelerating production, and increasing total recovery are compelling justifications for use of this system.

As illustrated in FIGURE 2, the components of the SCRAMSJ System 100 may include:

(a) one or more interval control valves 110 which provide an annulus to tubing flow path 102 and incorporates sensors 130 for reservoir data acquisition. The system 100 and the interval control valve 110 includes a choking device that isolate the reservoir from the production tubing 150. It will be understood by those skilled in the art that there is an inter-relationship between one control valve and another as one valve is directed to open another control valve may be directed to close;

(b) an HF Retrievable Production Packer 160 provides a tubing-to-casing seal and pressure barrier, isolates zones and/or laterals from the well bore 108 and allows passage of the umbilical 120. The packer 160 may be set using one-trip completion and installation and retrieval. The packer 160 is a hydraulically set packer that may be set using the system data communications and hydraulic power components. The system may also include other components as well known in the industry

including SCSSV 131, SCSSV control line 132, gas lift device 134, and disconnect device 136. It will be understood by those skilled in the art that the well bore log may be cased partially having an open hole completion or may be cased entirely. It will also be understood that the system may be used in multilateral completions;

(c) SEGNETJ Protocol Software is used to communicate with and power the SCRAMSJ system. The SEGNETJ software, accommodates third party products and provides a redundant system capable of by-passing failed units on a bus of the system;

(d) a dual flatback umbilical 120 which incorporates electro/hydraulic lines provides SEGNET communication and control and allows reservoir data acquired by the system to be transmitted to the surface.

Referring to FIGURE 3, the electro and hydraulic lines are protected by combining them into a reinforced flatback umbilical 120 that is run external to the production-tubing string (not shown). The flatback 120 comprises two galvanized mild steel bumper bars 121 and 122 and an incolony 1/4 inch tube 123 and 124. Inside tube 124 is a copper conductor 125. The flatback 120 is encased in a metal armor 126; and

(e) a surface control unit 160 operates completion tools, monitors the communications system and interfaces with other communication and control systems. It will be understood that an interrelationship exists between flow control devices as one is directed to open another may be directed to close.

A typical flow control apparatus for use in a subterranean well that is compatible with the SCRAMSJ system is illustrated and described in pending U.S. Patent Application Serial No. 08/898,567 filed July 21, 1997 by inventor Brett W. Boundin, the disclosure of which is incorporated by reference.

Referring now to blocks 21, 22, 23 of FIGURE 4, these blocks represent sensors as illustrated in FIGURE 2, or discussed in the background section (and/or as known in the art) used for collection of data such as pressure, temperature and volume, and 4D seismic. These sensors gather production/injection data from one or more wells that includes accurate pressure, temperature, viscosity, flow rate and compositional profiles available continuously on a real time basis.

Referring to box 38, in the system of the present invention, production/injection data is pre-processed using pressure transient analysis programs 24 in computer programs such as Saphir by Kappa Engineering or PTA by Geographix to

output reservoir permeability, reservoir pressure, permeability-feet and the distance to the reservoir boundaries.

Referring to box 40, geologic data including log, cores and SDL is collected with devices represented by blocks 25 and 26 as discussed in the background section, or by data sensors and collections well known in the art. Block 25 data is pre-processed as illustrated in block 26 using such computer programs Petroworks by Landmark Graphics, Prizm by Geographix and DPP by Halliburton to obtain water and oil saturations, porosity, and clay content. Block 25 data is also processed in stratigraphy programs as noted in block 26A by programs such as Stratworks by Landmark Graphics and may be further pre-processed to map the reservoir as noted in block 26B using a Z-Map program by Landmark Graphics.

Geologic data also includes seismic data obtained from collectors know in the art and represented by block 27 that may be conventional or real time 4D seismic data (as discussed in the background section). Seismic data is processed and interpreted as illustrated in block 28 by such programs as Seisworks and Earthcube by Landmark Graphics to obtain hydrocarbon indicators, stratigraphy and structure.

Output from blocks 26 and 28 is further pre-processed as illustrated in block 29 to obtain geostatistics using Sigmaview

by Landmark Graphics. Output from blocks 28, 29 and 26B are input into the Geocellular (Earthmodel) programs illustrated by block 30 and processed using the Stratamodel by Landmark Graphics. The resultant output of block 30 is then upscaled as noted in block 31 in Geolink by Landmark Graphics to obtain a reservoir simulation model.

Output from the upscaling program 31 is input into the data management function of block 32. Production/injection data collected by downhole sensors 21, seabed production sensors 22 and surface production sensors 23 may be input directly into the data management function 22 (as illustrated by the dotted lines) or pre-processed using pressure transient analysis as illustrated in block 22 as previously discussed. Data Management programs may include Openworks, Open/Explorer, TOW/cs and DSS32, all available from Landmark Graphics and Finder available from Geoquest.

Referring to box 39 of FIGURE 4, wherein there is disclosed iterative processing of data gathered by and stored in the data management program 32. The Reservoir Simulation program 33 uses data from the data management function 32, and can use data received from the Nodal Analysis program 35 to develop its simulation. The Reservoir Simulation program 33 can also output data to the Nodal Analysis program 35. Examples of Reservoir

Simulation programs include VIP by Landmark Graphics or Eclipse by Geoquest. The Material Balance program uses data from the reservoir simulation 33 and data management function 22 to determine hydrocarbon volumes, reservoir drive mechanisms and production profiles. One of the Material Balance programs known in the art is the MBAL program of Petroleum Experts.

The Nodal Analysis program 35 uses data from the Material Balance program 34 and Reservoir Simulation program 33 and other data such as wellbore configuration and surface facility configurations to determine rate versus pressure for various system configurations. Additionally, the Nodal Analysis program 35 shares information with the Reservoir simulation program 33, so that each program, Nodal Analysis 35 and Reservoir Simulation 33, may iteratively update and account for changes in the output of the other. Nodal Analysis programs include WEM by P.E. Moseley and Associates, GAP and Prosper by Petroleum Experts, and Openflow by Geographix.

Risked Economics programs 36 such as Aries or ResEV by Landmark Graphics determine the optimum field wide production/injection rate which may then be allocated back to individual wells. After production/injection by individual wells is calculated the reservoir management system of the present invention generates and transmits real time, though not

necessarily instantaneous, signals (designated generally at 50 in Figure 4) used to adjust interval control valves located in wells or adjust subsea control valves or surface production control valves to obtain the desired flow or injection rate. The desired production rate may be input directly back into the data management function 32 and actual production/injection from a well is compared to the target rate on a real time basis. Opening or closing a control valve 37 to the pre-determined position may have an almost immediate effect on the production/injection data collected by sensors represented by blocks 21, 22 and 33, however, on a long term basis, the reservoir as a whole is impacted and geologic data collected by sensors represented by blocks 25 and 27 will be affected (see dotted line from control valve 37). The present invention may be used to perform iterative calculations as illustrated in box 39 using the reservoir simulation program 23, material balance program 24, nodal analysis program 25 and risked economics program 26 to continuously calculate a desired field wide production rate and provide real time, though not necessarily instantaneous, control of production control devices.

FIGURE 4A is a generalized diagrammatic illustration of one exemplary embodiment of the system of FIGURE 4. In particular, the embodiment of FIGURE 4A includes a controller 400 coupled to

receive input information from information collectors 401. The controller 400 processes the information received from information collectors 401, and provides real time, though not necessarily instantaneous, output control signals to controlled equipment 402. The information collectors 401 can include, for example, the components illustrated at 38 and 40 in FIGURE 4. The controlled equipment 402 can include, for example, control valves such as illustrated at 37 in FIGURE 4. The controller 400 includes information (for example, data and program) storage and an information processor (CPU). The information storage can include a database for storing information received from the information collectors 401. The information processor is interconnected with the information storage such that controller 400 is capable, for example, of implementing the functions illustrated at 32-36 in FIGURE 4. As shown diagrammatically by broken line in FIGURE 4A, operation of the controlled equipment 402 affects conditions 404 (for example, wellbore conditions) which are monitored by the information collectors 401.

FIGURE 5 illustrates exemplary operations which can be performed by the controller 400 of FIGURE 4A to implement the data management function 32 of FIGURE 4. At 51, the production/injection (P/I) data both measured (for example, from box 38 of FIGURE 4) and simulated (for example, output from box

33 of FIGURE 4) is monitored in real time. Any variances in the P/I data are detected at 52. If variances are detected at 52, then at 53, the new P/I data is updated in real time to the Nodal Analysis and Material Balance functions 34 and 35 of FIGURE 4. At 54, geologic data, for example, from box 40 of FIGURE 4, is monitored in real time. If any changes in the geologic data are detected at 55, then at 56, the new geologic data is updated in real time to the Reservoir Simulation function 33 of FIGURE 4.

FIGURE 6 illustrates exemplary operations which can be performed by the controller 400 of FIGURE 4A to implement the Nodal Analysis function 35 and the Material Balance function 34 of FIGURE 4. At 61, the controller monitors for real time updates of the P/I data from the data management function 32. If any update is detected at 62, then conventional Nodal Analysis and Material Balance functions are performed at 63 using the real time updated P/I data. At 64, new parameters produced at 63 are updated in real time to the Reservoir Simulation function 33.

FIGURE 7 illustrates exemplary operations which can be performed by the controller 400 of FIGURE 4A to implement the Reservoir Simulation function 33 of FIGURE 4. At 71, the controller 400 monitors for a real time update of geologic data

from the data management function 32 or for a real time update of parameters output from either the Nodal Analysis function 35 or the Material Balance function 34 in FIGURE 4. If any of the aforementioned updates are detected at 72, then the updated information is used in conventional fashion at 73 to produce a new simulation forecast. Thereafter at 74, the new simulation forecast is compared to a forecast history (for example, a plurality of earlier simulation forecasts) and, if the new simulation is acceptable at 75 in view of the forecast history, then at 76 the new forecast is updated in real time to the Risked Economics function 36 of FIGURE 4.

Referring to the comparison and decision at 74 and 75, a new forecast could be rejected, for example, if it is considered to be too dissimilar from one or more earlier forecasts in the forecast history. If the new forecast is rejected at 75, then either another forecast is produced using the same updated information (see broken line at 78), or another real time update of the input information is awaited at 71. The broken line at 77 further indicates that the comparison and decision steps at 74 and 75 can be omitted as desired in some embodiments.

FIGURE 8 illustrates exemplary operations which can be performed by the controller 400 of FIGURE 4A to implement the Risked Economics function 36 of FIGURE 4. At 81, the controller

monitors for a real time update of the simulation forecast from the Reservoir Simulation function 33 of FIGURE 4. If any update is detected at 82, then the new forecast is used in conventional fashion to produce new best case settings for the controlled equipment 402. Thereafter at 84, equipment control signals such as illustrated at 50 in FIGURE 4 are produced in real time based on the new best case settings.

The following Table 1 includes a suite of tools (computer programs) that seamlessly interface with each other to generate a field wide production/injection forecast that is used to control production and injection in wells on a real time basis.

Table 1

Flow Chart Number	Input Data	Output Data	Computer Program (Commercial Name or Data Source)	Source of Program (name of company)
1. Downhole Prod. (across reservoir interval)	Pressure, temp, flow rates	Annulus (between tubing and casing) annular and tubing pressure (psi), temp (degrees, Fahrenheit, Centigrade), flow rate		
2. Seabed prod. (at subsea tree & subsea manifold)	Pressure, temp, flow rates	Pressure, temperature		
3. Surface prod. (at separators, compressors, manifolds, other surface equipment)	Pressure, temp, flow rates	Pressure, temperature		
4. Pressure Transient Analysis	Pressure, temp, flow rates	Reservoir Permeability Reservoir Pressure, Skin, distance to boundaries	Saphir PTA	Kappa Engineering Geographix
5. Logs, Cores, SDL		Pressure, temperature		
6. Log processing (interpretation)		Saturations Porosity Clay Content	Petroworks Prizm DPP	Landmark Graphics Geographix Halliburton
6A. Stratigraphy			Stratworks	Landmark Graphics
6B. Mapping			Z-Map	Landmark Graphics
7. Seismic Data				
8. Seismic Processing and Interpretation		Hydrocarbon indicators Stratigraphy	Seisworks Earthcube	Landmark Graphics

Flow Chart Number	Input Data	Output Data	Computer Program (Commercial Name or Data Source)	Source of Program (name of company)
		Structure		
9. Geostatistics			Sigmaview	Landmark Graphics
10. Geocellular			Stratamodel	Landmark Graphics
11. Upscaling			Geolink	Landmark Graphics Geoquest
12. Data Management, Data Repository	Outputs from other boxes		Finder Open works Open/Explore TOW/cs DSS32	Landmark Graphics
13. Reservoir simulation	Field or well production profile with time		VIP Eclipse	Landmark Graphics Geoquest
14. Material Balance	Fluid Saturations, Pressure reservoir geometry, temp, fluid physical prop., flow rate, reservoir physical properties	Hydrocarbon, in-place reservoir drive mechanism, production profile	MBAL	Petroleum Experts
15. Nodal Analysis, Reservoir and Fluid properties	Wellbore configurations, surface facility configurations	Rate vs. Pressure for various system and constraints	WEM GAP Prosper Openflow	P.E. Moseley & Associates Petroleum Experts Geographix
16. Risked Economics	Product Price Forecast, Revenue Working Interest, Discount Rate, Production Profile, Capital Expense, Operating Expense	Rate of return, net present value, payout, profit vs. investment ratio and desired field wide production rates.	Aries ResEV	Landmark Graphics
17. Control		Geometry		

Flow Chart Number	Input Data	Output Data	Computer Program (Commercial Name or Data Source)	Source of Program (name of company)
Production				

It will be understood by those skilled in the art that the practice of the present invention is not limited to the use of the programs disclosed in Table 1, or any of the aforementioned programs. These programs are merely examples of presently available programs which can be suitably enhanced for real time operations, and used to practice the invention.

It will be understood by those skilled in the art that the method and system of reservoir management may be used to optimize development of a newly discussed reservoir and is not limited to utility with previously developed reservoirs.

A preferred embodiment of the invention has been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiment disclosed, but is capable of numerous modifications without departing from the scope of the invention as claimed.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734